

Knauf UD Channels

Galvanized lightweight steel sections to be used as a perimeter channels for Knauf ceilings are cold-rolled from high-grade galvanized steel sheets that complies with EN 10327.

POWERED BY:

PREMIER

premier.partners



Knauf UD Channels EN-BS


Product Description

Galvanized lightweight steel sections to be used as a perimeter channels for Knauf ceilings are cold-rolled from high-grade galvanized steel sheets that complies with EN 10327.

Technical Data

Dimensions (mm)				Pallet Details		
Thickness (mm)	Web	Flange	Length	Meters Per Pack	Pieces Per Pack	Weight lm (Kg approx.)
0.5	22	23	3000	1440	480	0.37

Profile Section Details



Please contact our sales department for inquiries about storage and packing.

Note:

Knauf Head Office

Phone: +971 4 337 7170

Fax: +971 4 334 9659

P.O.Box: 112871, Dubai

info.uae@knauf.com

www.Knauf.ae

Knauf Manufacturing Plant

P.O.Box 50006 Ras Al Khaimah, U.A.E. Tel: +971 7 268 9837 Fax: +971 7 221 5301





Disclaimer:

The information provided in this leaflet is only intended to give guidance in selecting and using Knauf products. While we make every effort to ensure its accuracy, neither Knauf LLC and its branches nor any of tis employees or affiliates warrant or assume any legal liability or responsibility for the completeness or usefullness of any failure in installation or constructing any structure installation or building or caused by using this leaflet. Readers are adviced to independently verify this information prior to rely on it. In particular, readers must obtain appropriate advice on the use in specific structures, installations or buildings to ensure compliance with all regulations, including health and safety regulations. Knauf reserves the right to amend technical specification.

The constructional and structural properties, and characteristic building physics Knauf system can solely be ensured with the exclusive use Knauf system components, or other product expressly recommended by Knauf.