



POWERED BY:  
**PREMIER**  
premier.partners

Joint Treatment Materials

# Knauf Fill & Finish

Finishing, jointing, and skimming  
compound

Product-Data-Sheet

06/2024



**Build on us.**

## Product Description

Knauf Fill & Finish is a ready-mixed jointing compound for bedding tapes and finishing joints in drywall partitions and ceilings. Delivers up to Q4 finish.

## Areas of Application

Gypsum plasterboards, for bedding paper tape and finishing second and third coat of joints. For bedding paper-faced and metal corner beads and finishing joints.

## Key Benefits

- Easy-to-sand
- Ready-mixed for quick and easy application
- Fast drying time.
- Pure white finish
- Multiple layers can be used for added performance
- Can be used for full skim coating

## Compliance Standard

- ASTM C475M-17 – Standard Specification for Joint Compound and Joint Tape for Finishing Gypsum Board
- ASTM D3273-21 – Standard Test Method for Resistance to Growth of Mold on the Surface of Interior Coatings in an Environmental Chamber
- Tested for Low VOC & Formaldehyde content.

## Technical Information

Color	Weight (kg)	Approximate Coverage (m <sup>2</sup> )	Material Number
White	28	Jointing: 0.35 kg/m <sup>2</sup> Skimming (per mm of thickness): 1.6 kg/m <sup>2</sup>	845092

**JOINT TREATMENT MATERIALS****Sustainability****Substances of very high Concern (SVHC)**

At the time of publication, under REACH UK and REACH EU regulations, this product contain no SHVC. For more information please consult the Safety Data Sheet.

**Storage and Handling**

Store in a well-ventilated place. Keep away from heat and ignition sources. Protect from freezing, high temperature, and direct exposure to sunlight. Not to be used under 5° air or surface temperature.

**Packaging**

28kg plastic tub, 48pcs per pallet & wrapped with PE shrink wrap.

**Shelf Life/Service Life**

9 months.

**Health & Safety**

Ensure good ventilation, and wear personal protective equipment according to your risk assessment, see safety data sheet. Wear safety glasses with side shields due to splashing. When sanding, wear protective P2 dust mask. Impermeable protective gloves are recommended. Do not eat, drink, or smoke when using this product. Always wash hands after handling.

**Application /Installation**

Stir to an even consistency before use, may be diluted to suit individual preferences. Ensure, substrate is sound, dry, clean and free from oil and dust. Drying time dependent upon thickness, temperature, ventilation, air humidity and type of substrate. Average drying time approximately 3–5 hours before next coat. Before application of pain or wall paper, a suitable primer can be applied if required.

## Customer Service

UAE Tel: +971 4 33771700  
8:00 – 17:30 (UAE Time)  
Email:GCCcustomer.care@knauf.com  
Email: GCCtechnical.care@knauf.com



## HQ Address

Knauf LLC  
Units B9 & B10 – LIU 6  
Dubai Silicon Oasis  
Dubai, UAE

## Plant Address

P.O.Box 50006  
Ras Al Khaimah, U.A.E.  
Tel: +971 7 268 9837  
Fax: +971 7 221 5301



**Observe safety data sheet!**  
For safety data sheets and CE labelling see  
[www.Knauf.com](http://www.Knauf.com)



Tender texts for all Knauf systems and products with export functions for Word and PDF.



Videos for Knauf systems and products can be found under the following link:  
[youtube.com/knauf](https://youtube.com/knauf)



With the Knauf Infothek tablet app, all information and documents from Knauf GCC are now always up-to-date,

## Knauf GCC

Dubai, United arab Emirates

## Hotline

Phone: +9714-33-7170

[www.knauf.com](http://www.knauf.com)

Subject to technical changes. The current edition applies. The information contained herein corresponds to our current state of the art. The generally recognized rules of construction technology, relevant standards, guidelines and trade regulations must be observed by the contractor in addition to the processing instructions. Our warranty relates only to the flawless quality of our material. Consumption, quantity and execution data are empirical values that cannot be transferred without further ado in the event of deviating conditions. All rights reserved. Changes, reprinting and photo-mechanical and electronic reproduction, even in extracts, require our express authorization.

The structural, static and physical properties of Knauf systems can only be guaranteed if only Knauf system components or products recommended by Knauf are used.